



www.toplineonline.com 814-362-4626 / 800-458-6095

## PSI Service Ratings

Size (tube OD)	1/2 & 3/4	1	1-1/2	2	2-1/2	3	4	6	8	10	12	
13LAH		(Wing nut tightened to 25 in. lbs. torque)										
@70° F	1500	500	500	450	400	350	200	150	100	75	60	
@250° F	1200	250	250	250	200	150	125	75	50	50	-	
13MHHM		(Wing nut tightened to 25 in. lbs. torque)										
@70° F	-	500	500	450	400	350	200	150	100	75	60	
@250° F	-	250	250	250	200	150	125	75	50	50	-	
13MHHS		(Wing nut tightened to 25 in. lbs. torque)										
@70° F	-	600	600	550	450	350	300	150	-	-	-	
@250° F	-	300	300	275	225	175	150	75	-	-	-	
13MHP		(Wing tightened to 20 ft. lbs. torque)										
@70° F	1500	1500	1500	1000	1000	1000	1000	300	-	-	-	
@250° F	1200	1200	1200	800	800	800	800	200	-	-	-	
13I or 13IS												
@70° F	-	500	500	450	400	350	200	-	-	-	-	
@250° F	-	250	250	250	200	150	125	-	-	-	-	
13MHLA		(Screw tightened to maximum)										
@70° F	-	150	150	150	150	150	100	-	-	-	-	
@250° F	-	125	125	125	125	125	75	-	-	-	-	

Service Ratings are based on tests using standard 40MP-U Buna-N gaskets with proper expansion of ferrules, assembly of joints and absence of shock pressure.